

2006 Maintenance Schedule

Subject: 2006 Model Year Audi A4/S4 Avant, A4/S4 Sedan, and A4/S4 Cabriolet Maintenance Schedule

Number: AMS-05-19 Date: September 1, 2005

This Maintenance Service Circular AMS-05-19 dated September 1, 2005 supersedes Maintenance Service Circular AMS-05-18 dated August 5, 2005, containing Perfect Delivery Inspection Procedure, Inventory Maintenance Checklist, Suggested Repair Times and Scheduled Maintenance Intervals for the 2006 Model Year Audi A4/S4 Avant, A4/S4 Sedan, and A4/S4 Cabriolet Maintenance Schedule

Note: Perfect Delivery Inspection and Inventory Maintenance Checklist suggested maintenance times are applicable to United States only.

For states that require a manufacturer's statement regarding the delivery inspection procedure, the Perfect Delivery Inspection section of this Circular may be utilized for that purpose.

	<u>Page</u>
Perfect Delivery Inspection (PDI) Procedure	2 - 5
Inventory Maintenance Checklist	6
Suggested Repair Times	7
Scheduled Maintenance Intervals	8 - 10



Stock No	o.: Dealer Number:	R.O. No.:	Audi
V.I.N.: _		Road test mileage out: mileage in:	
☐ Rem	64 Technician Checklist (Part I) All Items must be nove full body cover (if installed) following TB Group 00 e: This is a 2-person task	e completed prior to customer delivery by an Audi Techi	nician.
Battery i Chec Chec Recc (If ne Verif foun Under th Visua	inspection: ck battery clamps for tightness. Tighten if required. ck the battery prior to starting engine with MCR340A ord MCR340A code: ecessary, recharge with the "inCharger" MCR940A) fy installation of all fuses. Re-install fuses removed during transportation or as id in PDI kit or ashtray as required.  he Hood Fluid Check and Inspection: hally inspect for leaks and loose components in engine compartment Audi 502.00), coolant, power steering and brake fluid levels – top off if required	<ul> <li>Verify operation of child safety lock-out switch –check re windows do not operate from the inside when on</li> <li>Check climate control functions and manual buttons- blo recirculation, defrost/defog. Verify display is set to corre</li> </ul>	dge) ar door interior latch and re- wer speeds, vent distributio
On Hoist	dshield washer/headlight washer. Fill to upper level and check concentration.  it Inspection: ck underside of vehicle for fluid leaks and loose components	□ Passenger side airbag: verify operation of Passive Occu □ Tire pressure monitoring - store current tire pressure val  Radio Inspection (Engine running outside- vehicle in PAI	ues (if equipped)
□ Rem □ Inspe □ Insta □ Sold	ck steering, boots, brake system, hoses, tires and wheels for damage nove suspension blocks (if installed) lect wheel bolts for proper torque using torque wrench all wheel bolt covers and center caps as supplied of or demo/display vehicles: Set tires to normal load tire pressure.  ord pressures here: Front Rear	<ul> <li>□ Radio/CD/Satellite Radio: Verify operation in AM/FM/CD using radio and steering wheel controls</li> <li>□ Verify operation of CD changer if equipped</li> <li>□ Verify installation of correct Satellite receiver (if equipped</li> <li>□ Set radio presets to local stations with strong signal receiver</li> </ul>	d) in radio
Trunk In Verif Instatrunk Set s Verif	chicle will be stored and not used as demo, inflate tires to 48-51psi inspection:  fy emergency repair tools and jack are installed securely in trunk tool kit all wheel bolt cover removal tool from PDI kit and wheel lock key (if applicable) k tool kit behind right side cover spare tire pressure. Record pressure here:  fy trunk opens and closes smoothly	Audi Navigation Plus Inspection (if equipped)  Navigation DVD: obtain DVD from Parts Dept. and instal the tilting faceplate of the Navigation Plus console. Verify Plus (on/off/tilt)  into Verify and set Language and Measurement Units in Car. Navigation location: set dealership location (for following road test)  MP3 SD card slots- insert card and test function	y operation of Audi Navigati Settings menu
Transpo With the Dead Inter	fy operation of trunk emergency release handle ort mode deactivation, DTC check, set service reminder VAS 5051 or VAS 5052: ctivate vehicle transport mode rrogate fault memory of all control modules, erase any DTC's service reminder t diagnostic log	Road Test Inspection:  □ Verify engine performance and acceleration. Listen for a  □ Automatic transmission: Verify proper operation includin- kickdown/Tiptronic®, and paddle shifters (as equipped)  □ Manual transmission: verify smooth clutch operation and abnormal noise. Verify clutch pedal starting interlock sw □ CVT transmission: Check for smooth operation/abnormal	g auto shift lock,  gear selection. Listen for itch. I noises/vibrations
Insta Test Test Insp Adju Turn light hom	Inspection: all permanent wiper blades unless vehicle is for inventory storage t windshield washers for aim and function t windshield wiper switch functions including intermittent and rain sensor function tect windshield wipers for proper cleaning, excessive noise, chattering or skipp ust if necessary.  n on headlights and test headlamp washers (if equipped) and headlight and fog a aiming. Verify operation of high/low beams/AUTO setting and coming tec/leaving home light operation. fy operation of daytime running lights (DRL) and switch on IP ck 2 remote keys: Central locking system/remote functions (check all buttons a	Verify quality of radio reception in AM and FM bands  Verify quality of radio reception in AM and FM bands  SAT radio (if equipped): press SAT button on radio and cruise control verify all functions  Climate control: Verify A/C / heat in all positions. Cycle in Seat heating: Inspect for proper operation	or drift/pull noise/vibration/pulsation verify reception recirculation and Econ.
door Verif Inspe	fy all 4 keys manually in driver's door and 2 masters in trunk lid lect all remote keys- press all buttons: lock/unlock/trunk release panic e: If battery has been replaced, it may be necessary to re-synchronize remotes	☐ Interrogate fault memory using VAS 5051 or VAS 5052☐ Record final mileage on checklist, sign checklist and obt signature. Remove top copy for RO and place remainde	er of checklist in glove box.
☐ Exte	uded in PDI) prior lights – check operation including turn signals, reverse lamps, parking ligh ker lights, hazard flashers, brake lights (including 3rd brake light), rear fog lam dle lights, and license plate lamps	ps, Apply Inventory Maintenance Sticker Perform 30 Day Maintenance Inspection every 30 days	
☐ Reco ☐ Chec ☐ Inspe ☐ Verif ☐ Verif seco	Inspection: ord start mileage on inspection checklist ck driver's door switches: Door locks/trunk release/fuel door release sect instrument cluster warning lights fy operation of central locking system locking/unlocking on all doors fy immobilizer functions: Verify that engine starts and runs for more than 5 onds, with all keys in ignition (Immobilizer test)	Checks performed:3060901  Perform final PDI check (Part II) prior to customer delive	
<ul><li>□ Verif</li><li>□ Mirro</li><li>□ Verif</li></ul>	ck both front seat power adjustments and seat memory operation fy operation of front/rear interior lights including doors, map and foot wells ors: inspect folding, adjustments, RH tilt in reverse, and memory fy cup holder and ashtray door operation ver windows: cycle all/verify operation including convenience open/close feature	I certify that all operations have been completed been prepared in accordance with Audi procedu standards.	
☐ Inspect	ect operation of lighter, ashtray door, aux. outlet under armrest and rear outlet clock and date to local time/date using correct format fy operation of all front and rear seat belts and latches fy glove box release and smooth opening/closing of glove box		
	brate rearview mirror compass to proper zone fy rearview mirror self-dimming function and lighting		



### A4 / S4 Final PDI Delivery Check and Detailer Perfect Delivery Inspection

Stock No.:		Dealer Number:		
V.I.N.:				
		PDI Check (Part I (in addition to Part I) if vehicle wa		showroom display, or used as a demo vehicle.
R.O. No.:	Date:	Mileage Start:	Mileage Finish:	Technician Name:
Record MCR340A (If necessary, recl Under the Hood Fluid Oil (Audi 502.00), required Windshield washed Necessary (Audi 502.00), required Windshield washed Set all tires to nor Record final press Install front licensor Trunk Inspection: Set spare tire press Exterior Inspection: Install permanent Test windshield was functions	harge with the "inCharger of Check and Inspection: coolant, power steering a per/headlight washer. Fill to mal load tire pressure.  Sures here: Fronte plate or filler panel (as resource.)  Record pressure having blades unless vehick ashers for aim and function of the proper switch functions included wipers for proper cleaning the cooleaning of the cooleaning	MCR940A  Ind brake fluid levels – top off if upper level and check concentration Rear equired in your market)  lere:	and functions i opening door)  Verify all 4 key Inspect all rem Note: If battery (included in PE  Inspect of the term of the t	n: iileage on inspection checklist date to local time/date using correct format monitoring - store current tire pressure values (if equipped)  tion:  performance and acceleration. Listen for abnormal noise/vibrations sten for abnormal road or wind noises. Check for squeaks/rattles. by/tires for pulling/vibration/noise/flat spotting. Int of steering wheel and check alignment for drift/pull and verify operation. Check for abnormal noise/vibration/pulsation
	<u> </u>			
WARNING:		se Accessories (R	•	e Performing
	Detail, As	This Can Discharg	je The Battery.	Please refer to Technical Bulletin
Perfect D	Delivery De	tailer Checklis	t	Group 00 for Detailer responsibilities, specific use of chemicals and for part
Must be complete  Exterior-Prior to		or to customer delivery		numbers to order materials.
☐ Remove protecti ☐ Wash/dry vehicle ☐ Inspect painted s ☐ If any defects (s ☐ Inspect body for ☐ Check interior fit ☐ Clean alloy whee ☐ Apply 3M Perfec ☐ Using 3M™ Glos  Under Hood—Prio	ve covering e exterior including ins surfaces/moldings/glas scratches/dings/dents/l paint defects and dan pors, sunroof, trunk, fre els/tires-remove any act t-lt™ Paste Wax ss Enhancer & Cleane r to Delivery	ont and rear windshield and all with the sive on wheels using 3M Genur Clay, clean front and rear wind	vindows for water leaks neral Purpose Adhesive Clear shield. After cleaning feel sur	
Important: Do no	ne compartment and r ot use dressing or che	emove excess water from grille micals containing silicone!	and nood area	
WARNING! Do r  Check upholster  Check for excess  Check all interior  Vacuum carpet  Check luggage or  Install front/rear	sunroof (if equipped)/ir protection/coverings/st not remove airbag war y/clean as required sive grease on seat tra r surfaces/compartmen compartment/vacuum floor mats (including lo	nterior rear view mirror and visor ickers/decals ning triangle/warning labels acks/clean as required nts (including sun visor/headline	r) for marks or fingerprints. Cl	lean as required
Final Quality Insp  Re-inspect vehice vehicle is to be of	le for surface scratche	es, swirl marks, paint chips, dent possible, inspect vehicle in shop	s, wax residue, dust, or lint prounder fluorescent lights or in	referably in area where h bright sunlight.
I certify that all ope	erations have been cor	npleted and this vehicle has bee	n prepared in accordance wit	th Audi procedures and Quality Standards.
Detailer Signature	e:		Date:	
Supervisor Signat	ture:		Date:	

Attn: Detailer

Following this procedure is necessary to claim PDI reimbursement at your dealership.

Please place this form in the glove box once completed.

### **A4 Cabriolet / S4 Cabriolet Perfect Delivery Inspection (PDI)**



Stock No.:	Dealer Number:		R	O. No.:		Audi
					 mileage in:	
Technician Che  ☐ Remove full body co	cklist (Part I) All Items must ver (if installed) following TB Group 00			_	_	nician
□ Check the battery prio Record MCR340A coc (If necessary, recharg) □ Verify installation of al found in PDI kit or ash Under the Hood Fluid Ch □ Visually inspect for lea □ Oil (Audi 502.00), coo	for tightness. Tighten if required. or to starting engine with MCR340A de: e with the "inCharger" MCR940A) If fuses. Re-install fuses removed during tran otray as required.	sportation or as		Multi-function steering wheel Steering column: check tilt/te Horn: check operation Check climate control functio ecirculation, defrost/defog. Check operation of heated re Sunshades: check operation	mming function and lighting I closing tools are present er operation of rear armrest cup c check operation of all switches elescope adjustments ons and manual buttons- blower s Verify display is set to correct coear seats	speeds, vent distribution untry settings
☐ Check underside of ve ☐ Check steering, boots ☐ Remove suspension b ☐ Inspect wheel bolts for ☐ Install wheel bolt cove ☐ Sold or demo/display v ☐ Record pressures here	chicle for fluid leaks and loose components, brake system, hoses, tires and wheels for dolocks (if installed) r proper torque using torque wrenchers and center caps as supplied vehicles: Set tires to normal load tire pressure: Front Rear d and not used as demo, inflate tires to 48-51	amage	. F . L . L . L . L . L . L . L . L . L . L	Radio/CD/Satellite Radio: Veusing radio and steering whe /erify operation of CD chang /erify installation of correct Set radio presets to local sta	ger if equipped Satellite receiver (if equipped) in tions with strong signal reception	radio
Trunk Inspection:  ☐ Verify emergency repairs of the proof of the pro	air tools and jack are installed securely in trur er removal tool from PDI kit and wheel lock ke ght side cover e. Record pressure here:	nk tool kit y (if applicable) into	t F	he tilting faceplate of the Na Plus (on/off/tilt) /erify and set Language and Navigation location: set deale oad test) MP3 SD card slots- insert ca /oice activation (if equipped)	vigation Plus console. Verify open I Measurement Units in Car/Setti ership location (for following back and test function	eration of Audi Navigation
With the VAS 5051 or VAS  Deactivate vehicle tran Interrogate fault memo Set service reminder Print diagnostic log  Exterior Inspection: Install permanent wipe Test windshield washe Test windshield wipe Adjust if necessary. Turn on headlights an light aiming. Verify op home/leaving home lig Verify operation of day Check 2 remote keys: functions including sea Verify all 4 keys manu Inspect all remote key Note: If battery has be (included in PDI) Exterior lights – check	er blades unless vehicle is for inventory storagers for aim and function switch functions including intermittent and rapers for proper cleaning, excessive noise, characters of high/low beams/AUTO setting and ght operation.  In the control locking system/remote functions (characters for proper cleaning) will opening door) ally in driver's door and 2 remote keys in trunties press all buttons: lock/unlock/trunk release ten replaced, it may be necessary to re-synchal synchological processing to peration.	ge in sensor functions attering or skipping. eadlight and fog coming eck all buttons and lik lid lock cylinder expanic aronize remotes aps, parking lights, at), rear fog lamps,	0	Verify engine performance at Automatic transmission: Veri kickdown/Tiptronic®, and par Manual transmission: verify some and the second of the	smooth clutch operation and geamal road or wind noises. Check ng/vibration/noise/flat spotting wheel and check alignment for dration. Check for abnormal noise ify hold and release on in AM and FM bands as SAT button on radio and verifyions heat in all positions. Cycle recircor proper operation oped): activate NAV and follow dining VAS 5051, 5051B or 5052 cklist, sign checklist and obtain Serifor RO and place remainder of the with remote and verify LED on the play/Inventory Storage or Demeta Sticker in Inspection every 30 days	rmal noise/vibrations. o shift lock, r selection. for squeaks/rattles. ift/pull /vibration/pulsation reception culation and Econ. ections back to dealersh ervice Manager's checklist in glove box. driver's window sill blinks
□ Inspect instrument clu □ Verify operation of cer □ Verify immobilizer fund seconds, with all keys □ Check both front seat □ Verify operation of fron □ Mirrors: inspect folding □ Verify cup holder and □ Power windows: cycle □ Inspect operation of lig □ Set clock and date to □ □ Verify operation of all	witches: Door locks/trunk release/fuel door rel	on nap and foot wells	I cobe sta	Perform final PDI check (Par electify that all operation election prepared in accorda andards.	s have been completed and ance with Audi procedures  Date Date Date Date Date Date Date Date	and quality

### A4 Cabriolet / S4 Cabriolet Final PDI Delivery Check / Detailer Perfect Delivery Inspection



Stock No.:Dealer Number:	
V.I.N.:	
Technician Final PDI Check (Part II) All Items on this inspection must be completed just prior to delivery (in addition to Part I) if vehicle	was stored in inventory, used for showroom display, or used as a demo vehicle.
R.O. No.: Date: Mileage Start:	Mileage Finish: Technician Name:
Battery inspection:  Check the battery prior to starting engine with MCR340A Record MCR340A code: (If necessary, recharge with the "inCharger" MCR940A  Under the Hood Fluid Check and Inspection: Top off oil (Audi 502.00), coolant, power steering and brake fluid levels – Windshield washer/headlight washer. Fill to upper level and check concentration.  On Hoist Inspection: Set all tires to normal tire pressure. Record final pressures here: Front Rear Install front license plate or filler panel (as required in your market)  Trunk Inspection: Set spare tire pressure. Record pressure here: Exterior Inspection: Install permanent wiper blades unless vehicle is for inventory storage Test windshield washers for aim and function Test windshield wiper switch functions including intermittent and rain sensor functions Inspect windshield wipers for proper cleaning, excessive noise, chattering or skipping.  Audi Detailer Perfect Delivery Checklist	<ul> <li>□ Check 2 remote keys: Central locking system/remote functions (check all buttons and functions including seat and mirror memory settings while opening door)</li> <li>□ Verify all 4 keys manually in driver's door and 2 remote keys in trunk lid</li> <li>□ Inspect all remote keys- press all buttons: lock/unlock/trunk release panic Note: If battery has been replaced, it may be necessary to re-synchronize remote (included in PDI)</li> <li>Interior Inspection:</li> <li>□ Record start mileage on inspection checklist</li> <li>□ Set clock and date to local time/date using correct format</li> <li>□ Tire pressure monitoring - store current tire pressure values (if equipped)</li> <li>Road Test Inspection:</li> <li>□ Verify engine performance and acceleration. Listen for abnormal noise/vibrations</li> <li>□ Ride quality: listen for abnormal road or wind noises. Check for squeaks/rattles.</li> <li>□ Check steering/tires for pulling/vibration/noise/flat spotting.</li> <li>□ Verify alignment of steering wheel and check alignment for drift/pull</li> <li>□ Apply brakes and verify operation. Check for abnormal noise/vibration/pulsation</li> <li>Post Road Test Inspection:</li> <li>□ Interrogate fault memory using VAS 5051, 5051B or VAS 5052</li> <li>□ Print Diagnostic Log</li> <li>□ Record final mileage on checklist, sign checklist</li> </ul>
Warning! Do Not Use Accessories (Radio, etc) while Performing Detail, A  Warning! Do Not Allow Convertible Top To Remain In A Partially Opened To Stop Functioning And Will Require Service.  Exterior  ☐ Remove protective covering and Rapguard™ ☐ Wash then dry vehicle exterior using clean chamois	
<ul> <li>□ Dry inside door jams and under hood and trunk</li> <li>□ Inspect all painted surfaces / moldings/glass for damage and remove any resi</li> <li>□ Inspect body for paint defects, dents, chips, scratches and damage</li> <li>Important! If any defects (scratches/dings/dents/body damage) are found, c</li> <li>□ Check interior floors, trunk, front and rear windshield and all windows for wat</li> <li>□ Clean alloy wheels/tires- remove any adhesive on wheels using 3M General Pt</li> <li>□ Wax exterior using 3M Perfect-it™ Paste Wax</li> <li>□ Clean front and rear windshield using 3M Gloss Enhancer™ &amp; Cleaner Clay-aft</li> </ul>	ontact your supervisor to arrange for immediate repair ter leaks urpose Adhesive Cleaner
Under Hood  ☐ Wipe down engine compartment and remove excessive water from grille and Important! Do not use chemicals or dressings containing silicone	hood areas
Interior  ☐ Clean all glass surfaces, interior rearview mirror and visor mirrors ☐ Remove all trim protection / coverings / stickers / decals ☐ Warning! DO NOT REMOVE AIRBAG WARNING TRAINGLE or WARNING LABEL ☐ Check interior upholstery, dashboard, sun visors and headliner for damage, so ☐ Check for excessive grease on seat tracks and clean as required ☐ Vacuum carpet and luggage compartment ☐ Install front and rear floor mats and check color match with interior	
Final Quality Check  ☐ Re-inspect vehicle for surface scratches, swirl marks, paint chips, dents, wax possible, inspect vehicle in shop under fluorescent lights or bright sunlight.  ☐ Sign checklist, and obtain supervisor's signature. Place completed form in gl	residue, dust, or lint preferably in area where vehicle is to be delivered. If this is not ove box for ABS delivery
I certify that all operations have been completed and this vehicle has been prepared in acc	cordance with Audi procedures and Quality Standards.
Detailer Signature: Date:	P Pontloy Dublishors

Supervisor Signature: \_

#### **30-Day Inventory Maintenance Checklist**



Stock #:						A			
VIN #									
Dealer # :									
	30	Days 60 Days 9				90 Days		Days	
Perform the 30-Day Inventory inspection <b>every 30 days of receipt from transporter or swap-in</b> (i.e. 30,60,90) until the vehicle is sold.	Date P	erformed:							
	ОК	Needs attention	ОК	Needs attention	ОК	Needs attention	ОК	Needs attention	
Vehicle Exterior:									
Body surfaces clean and free of environmental contaminants, damage, scratches, etc.									
If vehicle has rapguard or if body cover has been removed, open engine compartment and remove any debris from cowl									
Ensure proper tire inflations, check tire pressures and maintain storage pressure of 48-51psi (3.3-3.5 bar)									
Check battery condition- (static Voltage min. 12.5 Volts). Recharge if necessary. ${}^{\!\star}$									
Vehicle Interior:									
All accessories and lights are turned off.									
Interior surfaces clean and free of damage, scratches, etc.									
Start engine; while idling, open all vents and recirculation flaps and check A/C operation (for at least one minute).									
Test drive vehicle applying brakes several times (at least 4 times) at 20 mph (32 km/h) to clean brake rotors.									
During test drive, verify automatic and manual shift operation. Report any warning lights on instrument cluster to the Service Manager for repair.									
Verify disposable floor mats are in place.									
Affix next 30-day inventory sticker # W42INVSTKRA Replacement stickers are available through the Audi Technical Literature Ordering Center at 800-544-8021 8:00am-8:00pm EST, or on the Internet at www.audi.ddsltd.com 24 hours / 7 days a week.									
After test drive:									
Turn off all climate control systems and close all vents									
Verify windows, doors, hood, trunk lid and sunroof are fully closed									
Turn off all electrical consumers; verify solar panel is connected to the windshield properly and the power outlet or cigarette lighter.									
Verify all protective coverings are in place	Inspection P	erformed By:							
		•	·	•	,	•		•	

\* If the battery is dead, disconnected, or below 10 Volts, use VAS5051 / VAS 5052 to reset engine and transmission management systems to BASIC setting. Maintenance of new vehicle stock batteries is the dealership's responsibility. No replacement of batteries due to lack of maintenance, unless the battery is defective. Batteries will be debited unless a Midtronics printout is accompanied with the battery. Also, jump-starting may damage ECM.

Form # AUDI30CHECKLIST Revised 6-9-05

Notes:



**2006 Suggested Repair Times** 

Labor Operations	Vehicle:	A4/S4 Avant/ A4/S4 Sedan and A4/S4 Cabriolet
	Pre-Delivery Inspection	
01 01 00 26	Pre-Delivery Inspection	60
01 01 00 27	Delivery Inspection	60
	At 5,000 Miles (8,000 Km)	
03 05 00 78	1.8L Turbo	90
03 05 00 72	2.0L Turbo	100
03 05 00 75	3.0L	100
03 05 00 75	3.2L	100
03 05 00 76	4.2L	150
	At 15,000 Miles (25,000 Km)	
03 15 00 83	1.8L Turbo	125
03 15 00 70	2.0L Turbo	100
03 15 00 81	3.0L	125
03 15 00 81	3.2L	150
03 15 00 82	4.2L	190



**2006 Suggested Repair Times** 

Labor Operations	Vehicle:	A4/S4 Avant/ A4/S4 Sedan and A4/S4 Cabriolet
	At 25,000 Miles (40,000 Km)	
03 25 00 83	1.8L Turbo	80
03 25 00 70	2.0L Turbo	70
03 05 00 81	3.0L	80
03 05 00 81	3.2L	80
03 05 00 82	4.2L	115
	At 35,000 Miles (55,000 Km)	
03 31 00 83	1.8L Turbo	200
03 31 00 70	2.0L Turbo	170
03 31 00 81	3.0L	190
03 31 00 81	3.2L	215
03 31 00 82	4.2L	190
	At 45,000 Miles (72,000 Km)	
03 45 00 83	1.8L Turbo	80
03 45 00 70	2.0L Turbo	70
03 45 00 81	3.0L	80
03 45 00 81	3.2L	80
03 45 00 82	V8	115



Vehicle:	<u> </u>		<u>/ant/ A4/</u> 4/S4 Ca	S4 Sedan briolet	and
At 5,000 Miles (8,000 Km)	2.0 L	3.2L	1.8L	3.0L	4.2L
Engine Oil / Oil Filter: Change the oil and replace oil filter. (Caution: 2006 Audi models use only engine oil conforming to VW 502.00 specifications).	•	•	•	•	•
Windshield Wiper and Washer / Headlight washer: Check adjustment and function check fluid level and add if necessary.	•	•	•	•	•
Tires and Spare Wheel: Check for wear and damage. Rotate tires. Check the pressure.	•	•	•	•	•
Wiper arm pivots: Lubricate	•	•	•	•	•
Brake system: Check for damage and leaks. Check thickness of pads and brake fluid level	•	•	•	•	•
Service Reminder Indicator Display: Reset the display.	•	•	•	•	•



**2006 Scheduled Maintenance Intervals** 

Vehicle: A4/S4 Avant/ A4/S4 Sedan and A4/S4 Cabriolet			and .		
At 15,000 Mile (25,000 Km)	2.0 L	3.2L	1.8L	3.0L	4.2L
Engine Oil / Oil Filter: Change the oil and replace oil filter. (Caution: 2006 Audi models use only engine oil conforming to VW 502.00 specifications).	•	•	•	•	•
Cooling System: Check coolant level. Add coolant if necessary.	•	•	•	•	•
Exhaust System: Check for damage and leaks.	•	•	•	•	•
Engine, On-Board Diagnostic: Check Diagnostic Trouble Code Memory. Purge if necessary.	•	•	•	•	•
Engine: Check for leaks	•	•	•	•	•
Snow screen for air cleaner: Clean	•	•	•	•	N/A
Battery: Check electrolyte level. Add if necessary	•	•	•	•	•
Dust and pollen filter: Replace	•	•	•	•	•
Automatic transmission and final drive: Check for leaks	•	•	•	•	•
Manual transmission and final drive: Check for leaks	•	•	•	•	•
Sunroof: Clean guide rails and lubricate	•	•	•	•	•
Windshield Wiper and Washer / Headlight washer: Check adjustment and function check fluid level and add if necessary.	•	•	•	•	•
Wiper arm pivot points: Lubricate	•	•	•	•	•
Tires and Spare Wheel: Check for wear and damage. Check pressure.	•	•	•	•	•
Tire repair set: Check renewal date. (Where applicable)	•	•	•	•	•
Service Reminder Indicator Display: Reset display.	•	•	•	•	•

### Page 10 of 19



Vehicle:	<u>A4</u>		nt/ A4/S4 S4 Cabri		<u>and</u>
At 15,000 Mile (25,000 Km) (cont.)	2.0 L	3.2L	1.8L	3.0L	4.2L
Lights: Check lights. Check Headlight adjustment	•	•	•	•	•
Brake System: Check for damage and leaks. Check thickness of pads and brake fluid level.	•	•	•	•	•
Front and rear axle: Check dust seals on ball joints and tie rod ends. Check tie rods	•	•	•	•	•
Front and rear axle: Check excessive play	•	•	•	•	•
Drive Shafts: Check boots.	•	•	•	•	•
Visual check: Check undercarriage for damage	•	•	•	•	•
Doors: Lubricate door hinge mechanism.	•	•	•	•	•
Road Test: Check braking, kick-down, steering, electrical, heating & ventilation systems, air conditioning, Automatic Shift Lock (ASL) operation and power accessories	•	•	•	•	•
At 25,000 Miles (40,000 Km)	2.0 L	3.2L	1.8L	3.0L	4.2L
Perform 5,000 Mile (8,000 km) Maintenance Service. (Except: rotate tires)	•	•	•	•	•



### 2006 Scheduled Maintenance Intervals

Vehicle:	<u>A4/S</u>	4 Avant/ A4/S4	A4/S4 Cabric		and
At 35,000 Miles (55,000 Km)	2.0 L	3.2L	1.8L	3.0L	4.2L
Engine Oil / Oil Filter: Change oil and replace oil filter. (Caution: 2006 Audi models use only engine oil conforming to VW 502.00 specifications).	•	•	•	•	•
Cooling System: Check coolant level. Add coolant if necessary.	•	•	•	•	•
Exhaust System: Check for damage and leaks.	•	•	•	•	•
Engine, On-Board Diagnostic: Check Diagnostic Trouble Code Memory. Purge if necessary.	•	•	•	•	•
Engine: Check for leaks	•	•	•	•	•
Battery: Check electrolyte level. Add if necessary	•	•	•	•	•
Dust and pollen filter for: Replace	•	•	•	•	•
Sunroof: Clean guide rails and lubricate	•	•	•	•	•
Windshield Wiper and Washer / Headlight washer: Check adjustment and function check fluid level and add if necessary.	•	•	•	•	•
Wiper arm pivot point: Lubricate	•	•	•	•	•
Automatic transmission and final drive: Check for leaks	•	•	•	•	•
Manual transmission and final drive: Check for leaks	•	•	•	•	•
Tires and Spare Wheel: Check for wear and damage. Check pressure.	•	•	•	•	•
Tire repair set: Check renewal date. (Where applicable)	•	•	•	•	•
Doors: Lubricate door hinge mechanism.	•	•	•	•	•
Service Reminder Indicator Display: Reset display.	•	•	•	•	•
Brake System: Check for damage and leaks. Check thickness of pads and brake fluid level.	•	•	•	•	•

### Page 12 of 19



Vehicle:	A4/S4 Avant/ A4/S4 Sedan and A4/S4 Cabriolet					
At 35,000 Miles (55,000 Km) (cont.)	2.0 L	3.2L	1.8L	3.0L	4.2L	
Front and rear axle: Check dust seals on ball joints and tie rod ends. Check tie rods	•	•	•	•	•	
Front and rear axle: Check excessive play	•	•	•	•	•	
Drive Shafts: Check boots.	•	•	•	•	•	
Snow screen for air cleaner: Clean	•	•	•	•	N/A	
Power steering: Check fluid level and add if necessary	•	•	•	•	•	
Spark plugs: Replace	N/A	N/A	•	•	N/A	
Continuously variable transmission (multitronic™): Change ATF	•	•	•	N/A	N/A	
Visual check: Check undercarriage for damage	•	•	•	•	•	
Lights: Check lights. Check Headlight adjustment	•	•	•	•	•	
Road Test: Check braking, kick-down, steering, electrical, heating & ventilation systems, air conditioning, Automatic Shift Lock (ASL) operation and power accessories	•	•	•	•	•	
At 45,000 Miles (72,000 Km)	2.0 L	3.2L	1.8L	3.0L	4.2L	
Perform 5,000 Mile (8,000 km) Maintenance Service. (Except: rotate tires)	•	•	•	•	•	



### 2006 Scheduled Maintenance Intervals

Vehicle:	<u>A</u> 4	A4/S4 Avant/ A4/S4 Sedan and A4/S4 Cabriolet					
At 55,000 Mile (85,000 Km)	2.0 L	3.2L	1.8L	3.0L	4.2L		
Engine Oil / Oil Filter: Change the oil and replace oil filter. (Caution: 2006 Audi models use only engine oil conforming to VW 502.00 specifications).	•	•	•	•	•		
Cooling System: Check coolant level. Add coolant if necessary.	•	•	•	•	•		
Exhaust System: Check for damage and leaks.	•	•	•	•	•		
Engine, On-Board Diagnostic: Check Diagnostic Trouble Code Memory. Purge if necessary.	•	•	•	•	•		
Engine: Check for leaks	•	•	•	•	•		
Snow screen for air cleaner: Clean	•	•	•	•	N/A		
Air cleaner: Clean housing and replace filter element	•	•	•	•	•		
Battery: Check electrolyte level. Add if necessary	•	•	•	•	•		
Dust and pollen filter: Replace	•	•	•	•	•		
Automatic transmission and final drive: Check for leaks	•	•	•	•	•		
Manual transmission and final drive: Check for leaks	•	•	•	•	•		
Sunroof: Clean guide rails and lubricate	•	•	•	•	•		
Windshield Wiper and Washer / Headlight washer: Check adjustment and function check fluid level and add if necessary.	•	•	•	•	•		
Wiper arm pivot points: Lubricate	•	•	•	•	•		
Service Reminder Indicator Display: Reset	•	•	•	•	•		

### Page 14 of 19



Vehicle:	<u>A4/S</u>	A4/S4 Avant/ A4/S4 Sedan and A4/S4 Cabriolet				
At 55,000 Mile (85,000 Km) (cont.)	2.0 L	3.2L	1.8L	3.0L	4.2L	
Front and Rear Axle: Check dust seals on ball joints and tie rod ends. Check tie rods.	•	•	•	•	•	
Front and Rear Axle: Check excessive play	•	•	•	•	•	
Drive Shafts: Check boots.	•	•	•	•	•	
Spark plugs: Replace	•	•	N/A	N/A	•	
Lights: Check the lights. Check Headlight adjustment	•	•	•	•	•	
Brake System: Check for damage and leaks. Check thickness of pads and brake fluid level.	•	•	•	•	•	
Tire repair set: Check renewal date (Where applicable)	•	•	•	•	•	
Tires and Spare Wheel: Check for wear and damage. Check pressure.	•	•	•	•	•	
Visual check: Check undercarriage for damage	•	•	•	•	•	
Doors: Lubricate door hinge mechanism.	•	•	•	•	•	
Road Test: Check braking, kick-down, steering, electrical, heating & ventilation systems, air conditioning, Automatic Shift Lock (ASL) operation and power accessories	•	•	•	•	•	
At 65,000 Mile (100,000 Km)	2.0 L	3.2L	1.8L	3.0L	4.2L	
Perform 5,000 Mile (8,000 km) Maintenance Service. (Except: rotate tires)	•	•	•	•	•	



### 2006 Scheduled Maintenance Intervals

Vehicle:	A4/S4 Avant/ A4/S4 Sedan and A4/S4 Cabriolet				
At 75,000 Mile (115,000 Km)	2.0 L	3.2L	1.8L	3.0L	4.2L
Engine Oil / Oil Filter: Change oil and replace oil filter. (Caution: 2006 Audi models use only engine oil conforming to VW 502.00 specifications).	•	•	•	•	•
Cooling System: Check coolant level. Add coolant if necessary.	•	•	•	•	•
Exhaust System: Check for damage and leaks.	•	•	•	•	•
Engine, On-Board Diagnostic: Check Diagnostic Trouble Code Memory. Purge if necessary.	•	•	•	•	•
Engine: Check for leaks	•	•	•	•	•
Snow screen for air cleaner: Clean	•	•	•	•	N/A
Battery: Check electrolyte level. Add if necessary	•	•	•	•	•
Dust and pollen filter: Replace	•	•	•	•	•
Manual transmission and final drive: Check for leaks	•	•	•	•	•
Automatic transmission and final drive: Check for leaks	•	•	•	•	•
Sunroof: Clean guide rails and lubricate	•	•	•	•	•
Windshield Wiper and Washer / Headlight washer: Check adjustment and function check fluid level and add if necessary.	•	•	•	•	•
Wiper arm pivot points: Lubricate	•	•	•	•	•
Tires and Spare Wheel: Check for wear and damage. Check pressure.	•	•	•	•	•
Tire repair set: Check renewal date. (Where applicable)	•	•	•	•	•
Service Reminder Indicator Display: Reset display.	•	•	•	•	•

### Page 16 of 19



Vehicle	: A4/S4 Avant/ A4/S4 Sedan and A4/S4 Cabriolet							
At 75,000 Mile (115,000 Km) (cont.)	2.0 L	3.2L	1.8L	3.0L	4.2L			
Lights: Check the lights. Check Headlight adjustment	•	•	•	•	•			
Brake System: Check for damage and leaks. Check thickness of pads and brake fluid level.	•	•	•	•	•			
Drive Shafts: Check boots.	•	•	•	•	•			
Doors: Lubricate door hinge mechanism.	•	•	•	•	•			
Visual Check: Check undercarriage for damage.	•	•	•	•	•			
Power steering: Check fluid level .	•	•	•	•	•			
Spark plugs: Replace.	N/A	N/A	•	•	N/A			
Continuously variable transmission (multitronic™): Change ATF	•	•	•	N/A	N/A			
Ribbed belt: Replace.	N/A	N/A	•	N/A	•			
Ribbed belt: Check condition.	•	•	N/A	•	N/A			
Timing belt: Replace.	•	N/A	•	•	N/A			
Timing belt tensioning system, dampening pulleys, and idler pulleys: Check condition.	•	N/A	N/A	N/A	N/A			
Front and Rear Axle: Check excessive play.	•	•	•	•	•			
Front and Rear Axle: Check dust seals on ball joints and tie rod ends. Check tie rods.	•	•	•	•	•			
Road Test: Check braking, kick-down, steering, electrical, heating & ventilation systems, air conditioning, Automatic Shift Lock (ASL) operation and power accessories.	•	•	•	•	•			



2006 Scheduled Maintenance Intervals

Vehicle:	A4/S4 Avant/ A4/S4 Sedan and A4/S4 Cabriolet				n and
At 85,000 Mile (130,000 Km)	2.0 L	3.2L	1.8L	3.0L	4.2L
Perform 5,000 Mile (8,000 km) Maintenance Service. (Except: rotate tires)	•	•	•	•	•
At 95,000 Mile (145,000 Km)	2.0 L	3.2L	1.8L	3.0L	4.2L
Engine Oil / Oil Filter: Change oil and replace oil filter. (Caution: 2006 Audi models use only engine oil conforming to VW 502.00 specifications).	•	•	•	•	•
Cooling System: Check coolant level. Add coolant if necessary.	•	•	•	•	•
Exhaust System: Check for damage and leaks.	•	•	•	•	•
Engine, On-Board Diagnostic: Check Diagnostic Trouble Code Memory. Purge if necessary.	•	•	•	•	•
Engine: Check for leaks.	•	•	•	•	•
Snow screen for air cleaner: Clean .	•	•	•	•	N/A
Battery: Check electrolyte level. Add if necessary.	•	•	•	•	•
Dust and pollen filter: Replace.	•	•	•	•	•
Automatic transmission and final drive: Check for leaks.	•	•	•	•	•
Manual transmission and final drive: Check for leaks.	•	•	•	•	•
Sunroof: Clean guide rails and lubricate.	•	•	•	•	•
Windshield Wiper and Washer / Headlight washer: Check adjustment and function check fluid level and add if necessary.	•	•	•	•	•
Wiper arm pivot points: Lubricate.	•	•	•	•	•
Tires and Spare Wheel: Check for wear and damage. Check pressure.	•	•	•	•	•
Tire repair set: Check renewal date. (Where applicable)	•	•	•	•	•

### Page 18 of 19



Vehicle:	A4/S4 Avant/ A4/S4 Sedan and A4/S4 Cabriolet				
At 95,000 Mile (145,000 Km) (cont.)	2.0 L	3.2L	1.8L	3.0L	4.2L
Service Reminder Indicator Display: Reset the display.	•	•	•	•	•
Lights: Check lights. Check Headlight adjustment	•	•	•	•	•
Brake System: Check for damage and leaks. Check thickness of pads and brake fluid level.	•	•	•	•	•
Front and Rear Axle: Check dust seals on ball joints and tie rod ends. Check tie rods	•	•	•	•	•
Front and Rear Axle: Check excessive play	•	•	•	•	•
Drive Shafts: Check boots.	•	•	•	•	•
Doors: Lubricate door hinge mechanism.	•	•	•	•	•
Visual check: Check undercarriage for damage	•	•	•	•	•
Road Test: Check braking, kick-down, steering, electrical, heating & ventilation systems, air conditioning, Automatic Shift Lock (ASL) operation and power accessories	•	•	•	•	•
Every 2 years, <u>regardless</u> of miles (kilometers).	2.0 L	3.2L	1.8L	3.0L	4.2L
Brake Fluid: Replace brake fluid.	•	•	•	•	•
Cloth top: Check function and roll-over protection with cloth top down (Audi A4/S4 Cabriolet)	•	•	•	•	•