

2007 Scheduled Maintenance Intervals

Miles (in thousands)	5/25/45/65/85/105	15/55/95	35/75
Kilometres (in thousands)	8/40/70/100/130/160	25/85/145	55/115
Engine Oil – change oil and replace filter	•	•	•
Wiper/Washer/Headlight Washer – check adjustment and function,	•	•	•
add fluid if necessary			
Tires and Spare – check for wear and damage, check pressure	•		
- check for wear and damage, check pressure and renewal date		•	•
of tire set (where applicable)	l n		
of tire set (where applicable) Tires – rotate Service Reminder Display – reset Brake System – check for damage, leaks, pad thickness fluid level	Bentley Polyblic		
Service Reminder Display – reset	• "Shers.co	•	•
Brake System – check for damage, leaks, pad thickness fluid level	• 20/17 /	St Benneye	•
Wiper Arm Pivot Points – lubricate	•	y ⊗ •	•
Cooling System – check level, add if necessary		71%.	•
Exhaust System – check for damage and leaks		- Lo	•
Engine On Board Diagnostics – check faul memory		Cept Audi Q7	Except Audi Q7
Engine Compartment – check for leaks		0	•
Battery – check and replace if necessary		• vicom	•
Dust and Pollen Filter – replace			•
Automatic Transmission and Final Deve – check for leaks		<u> </u>	•
Manual Transmission and Final Drive – check for leaks		TO TO	•
DSG (direct shift gearbox) – changeoil and replace filter element		entley	
		70	A3 only
Haldex Clutch – change oil		ublishers	A3 only
		<u>s</u>	•
Front and Rear Axle – check for excessive play, check dust seals on ball joints			•
and tie rod ends		O O O O O O O O O O O O O O O O O O O	
Lights – check all lights, check headlight adjustment		- Ad dilly	•
Drive Shaft Boots – check		[B]	•
Doors – lubricate doors, check straps 6		A8 onl	•
Spark Plugs – replace at 35,000 miles on years, whichever occurs first.		ntohu.	35K only: 3.2L VR6 and 6.0L
Then, every 40,000 miles or years, whichever occurs first.			engines
– replace at 55,000 miles or 6 pears, whichever occurs first.		55K only: except 3.2L VR6 and 6.0L engines	
Then, every 60,000 miles or 6 years, whichever occurs first.			
– replace at 75,000 miles		ho ₂	75K only: 3.2L VR6 and 6.0L engines
Continuously Variable Transmission (multitronic) - Anange ATF	. 16	N .	•
Power Steering Fluid – check, add if necessary	1 Benne		•
Power Steering Fluid – check, add if necessary Air Cleaner – clean housing, replace filter element Ribbed V Belt and Tensioner – check condition and replace if necessary	moo.erahailduq _{kahna} g i _k	 55K only: A3, A4, A6, S6, S8, Audi Q7 3.6L, A8 4.2L 	35K only: RS 4, A8 6.0L 75K only: RS 4, Audi Q7 4.2L, A8 6.0L
Ribbed V Belt and Tensioner – check condition and replace if necessary		RS 4 only	RS 4, Audi Q7 3.6L, A8 6.0L only
Ribbed V Belt – check condition and replace if necessary. Check tension of			75K only: 2.0TFSI, 3.2L, 4.2L FSI, 5.2L
belt drive with a manual tensioner and retension if necessary.			3.2L, 4.2L FSI, 5.2L
Ribbed V Belt - replace			75K only: S4
Snow Screen for Air Cleaner – clean		• A4, A6 only	A4, A6 only
Underbody – check for damage and leaks		•	•
Road Test – check braking, kick-down, steering, electrical, heating and			•
ventilation systems, air conditioning, shift lock operation and power accessories		, i	
Rear Lid Hinges – lubricate		A8 only	A8 only
nour Ela lilligue Tabilloute		Ac only	Ac only

At 110K miles (175km) replace timing belt (2.0TFSI engine only). Check condition of timing belt tensioning system, dampening pulleys, and idler pulleys and replace if necessary (2.0TFSI engine only).

Brake Fluid – replace every 2 years regardless of mileage.

Cloth Top – check function and rollover protection every 2 years regardless of mileage (Audi A4 Cabriolet only).

Audi of America, Inc. believes the information and specifications to be correct at the time of printing. Specifications, maintenance intervals, standard features and options subject to change without notice.

Revised 10/27/2008